

LIMITLESS CREATIVITY

Stratasys J850 TechStyle™ 3D printer is making waves with its revolutionary 3DFashion™ printing technology. For the first time ever, 3D algorithms can be printed direct-to-textile, creating fascinating illusions with color and light.

Digital 3D design and aesthetics can now be created by a computer-generated design flow, that cannot be completed manually. In industries such as fashion and automotive interiors, TechStyle enables designers to truly unleash their imagination with limitless creations and unparalleled flexibility and industry-certified materials. With multiple advantages over traditional forms of design, designers can create fantastic optical illusionary effects, direct to textile and garments, in clear print and in full color.





CERTIFIED MATERIALS

Printing with the TechStyle 3D printer can be done safely and responsibly, thanks to the patent-pending VeroEco™ Flex family of materials. These semi-flexible, soft-to-thetouch materials are the perfect choice for direct-to-textile 3D printing, boasting vivid colors and robust adhesion to multiple types of fabrics, so garments stay intact through most standard machine-wash cycles. Not only do they provide excellent flexibility and durability, but they are also at the forefront of sustainability, compliant with industry Standard RSL (Restricted Substances List for Finished Products).







DESIGN FREEDOM

You're looking at a paradigm shift in the intersection of technology and fashion. Elevate your designs, captivate your audience, and embrace the future of bespoke, sustainable fashion with TechStyle. Empower your creativity, customize fashion and automotive interiors, reduce waste and streamline production. Experience a new level of design freedom, with TechStyle's virtually limitless color palette, with over 600K available colors in both matte and glossy finishes, TechStyle can print up to 7 different materials directly onto fabric at the same time, with varying transparency, textures and colors that will support any design. Easily print with your favorite design software from the multitude of compatible options and output your file direct to GrabCAD Print™ for printing.

Greta Oto DressBy threeASFOUR and Travis Fitch
In collaboration with STRATASYS

UNPARALLELED PRODUCTIVITY

The TechStyle 3D printer is designed for optimal productivity, featuring a high-efficiency, long-lasting LED unit. Experience exceptional productivity right from the moment you switch it on and begin printing. Its user-friendly workflow makes refining your creations a breeze, and an interchangeable tray enables lightning-fast printing with minimal downtime.

UNMATCHED CAPABILITIES

TechStyle™ Fabric Alignment Station

The only tool available for high-end fashion designers seeking precision and innovation. This station offers a game-changing solution for aligning 2D patterns with intricate 3D designs or aligning within defined areas on a garment such as pockets, patches and flaps as well as 3D designs on specific sections of a garment created using stitching techniques such as embroidery and thin ribbons or strips of material.

D2G Trays Kit

Direct-to-Garment 3D printing that repurposes fashion design by allowing you to print directly onto finished garments. The kit is available as an add-on accessory and is provided with two trays in different sizes for wider garments such as jackets and shirts and narrower garments such as pants and jeans to customize fashion and reduce waste.

2-mode capacity

Enabling direct to textile printing as well as 3D models for fashion accessories, such as buttons, cufflinks, and bag clips, can also be printed, to a maximum height of 50mm.

Interchangeable Tray

Quickly swap out one tray for another for lightning-fast production runs without unnecessary down time. It's easy to switch trays quickly and effortlessly, ensuring your projects are printed quickly and efficiently every time.

Fabric Analyzer

Another unique feature of TechStyle, which analyzes a fabric sample for digital design optimization, reducing time and costs in preproduction.

VeroEco™ Bond 60

This digital primer enables seamless adhesion of 3D printed designs onto many types of fabric while meeting meets the exact standards of the high-end fashion industry

Adhesion Optimization

Enhances TechStyle's unmatched flexible printing capabilities, enabling adaptable workflows for a broad range of fabrics and substrates. This feature, coupled with the comprehensive support of GrabCADTM Print software, streamlines the entire printing process, from conceptual design to the final production of 3D printed designs.



EFFICIENT WORKFLOW

Streamline your workflow with GrabCAD Print software by printing directly from your favorite professional CAD formats, with or without the addition of advanced rendering software.

Eliminate time-consuming painting or trial-and-error color matching with a single click step in GrabCAD Print. Use smart default settings, tooltips, and notifications to guide you through a seamless printing process. Work with detailed views of your model, tray, and slice preview so you can make any necessary adjustments before going to print.

The large, seven-material capacity of the Stratasys J850 TechStyle printer means you can load your most used resins and avoid downtime associated with material changeovers

GrabCAD Print software is an Industry 4.0 compatible system that will fully integrate with manufacturing execution systems (MES) and your digitized production floor.



The Flower of LifeBy Ada Hefetz in collaboration with STRATASYS

MINDFUL MANUFACTURING

Stratasys J850 TechStyle 3D printer promotes Mindful Manufacturing™, emphasizing low-volume production to minimize oversupply and reduce waste. Our commitment extends beyond mere compliance - we are leading the additive manufacturing industry forward towards improving environmental impact. We believe that meaningful long-term growth and success rests upon three pillars: Environmental Action, Social Impact, and Ethical Governance.

Responsible consumption, industry innovation and revised supply chains go hand-in hand with 3D printing technologies. We are committed to streamlining sustainable fashion by enabling on-demand production to minimize overproduction and waste, rejuvenating old garments with new designs to support a circular economy, and using industry-certified materials to reduce the environmental footprint. This is fashion forward; 3D Printing a Better Tomorrow™ today.



DIGI DressBy Karim Rashid
Designed for the STRATASYS Reflection Collection

ALL THE SPECS YOU NEED

Materials	Unlimited number of digital materials including:				
Digital Model Materials	Over 600K available colors in both matte and glossy finishes				
	 Translucent color tints Flexible tactile materials in a variety of textures and colors 				
			Managara Mali	I V F TM D I	
Industry Compliant Materials	VeroEco™Flex family of semi-flexible materials: Clear, Black and VeroEco™ ContactFlex.	, White, Cyan	, Magenta, Yel	low, VeroEco''' Bond (00
	VeroEco Flex family of materials are in compliance with RSL (Restricted Substances List for Finished Products) industry standards.				
	Printed Textile Testing*	100% Cotton	100% Polyester	50/50% Cotton Polyester	Line
	Color fastness for washing at 40°C (1-5) ISO 105-C06:2010	5	5	5	5
	Color fastness for washing at 60°C (1-5) ISO 105-C06:2010	5	5	5	5
	Adhesion to washing at 40°C & 60°C ISO 105-C06:2010	Pass	Pass	Pass	Pas
	Color fastness to rubbing (wet 50 rubs) ISO 11640:2018	Pass	Pass	Pass	Pas
	Color fastness to rubbing (dry 150 rubs) ISO 11640:2018	Pass	Pass	Pass	Pas
	Abrasion resistance (Martindale) ISO 12947-2:2016	Pass	Pass	Pass	Pas
Standard Materials	VeroUltra™ & VeroVivid™ family of opaque and transparent m			nd vibrant colors	
	• Agilus30™ family of flexible materials: Clear, Black, White, 0	Cyan, Magent	ta and Yellow		
Support Materials	SUP705 [™] (water jet removable) & 705B				
Support Materials Hardware	SUP705 [™] (water jet removable) & 705B				
	SUP705" (water jet removable) & 705B Fabric Size Handling: min 560 x 460mm; max 2 x 2m				
	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm				
Hardware	Fabric Size Handling: min 560 x 460mm; max 2 x 2m				
Hardware	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm	oric up to 2m	2		
Hardware Build Size	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs	oric up to 2m	2		
Hardware Build Size Effective Printing Area	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab	oric up to 2m	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fabric Horizontal build layers down to 27-micron (0.001 in.)	oric up to 2m	2		
Hardware Build Size Effective Printing Area Layer Thickness	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fabric Horizontal build layers down to 27-micron (0.001 in.) Windows 10	oric up to 2m	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fabric Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP	·	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94)	·	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fat Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet:	8 lbs.)	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs	8 lbs.)	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs) Fabric Alignment Station:	8 lbs.)	2		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fat Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg	8 lbs.) s.)			
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7	8 lbs.) s.) ''0% (non-con	densing)		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 5	8 lbs.) s.) ''0% (non-con	densing)		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements Regulatory Compliance	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fat Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 50 CE, FCC, EAC, RCM, R-NZ1	8 lbs.) s.) ''0% (non-con	densing)		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 50 CE, FCC, EAC, RCM, R-NZ1 GrabCAD Print - GrabCAD Printer Connectivity SDK	8 lbs.) s.) 70% (non-con 0–60 Hz, 7 A	densing)		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements Regulatory Compliance	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 50 CE, FCC, EAC, RCM, R-NZ1 GrabCAD Print - GrabCAD Printer Connectivity SDK High Mix: up to 7 base resins, 27-micron (0.001 in.) resoluti	8 lbs.) s.) 70% (non-con 0-60 Hz, 7 A	densing)		
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements Regulatory Compliance Software	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 50 CE, FCC, EAC, RCM, R-NZ1 GrabCAD Print - GrabCAD Printer Connectivity SDK	8 lbs.) 70% (non-con 0-60 Hz, 7 A on ution sions, for mod	densing) , 1 phase dels printed wi		sed on
Hardware Build Size Effective Printing Area Layer Thickness Workstation Compatibility Network Connectivity System Size and Weight Operating Conditions Power Requirements Regulatory Compliance Software	Fabric Size Handling: min 560 x 460mm; max 2 x 2m Fabric Thickness: 0.1-3.0mm Interchangeable Tray for smooth production runs 460 x 360 x 50 mm (18.1 x 14.2 x 1.9 in) on a stretch of fab Horizontal build layers down to 27-micron (0.001 in.) Windows 10 LAN - TCP/IP Industry 4.0 Compliance J850 TechStyle System: 1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (94 J850 TechStyle Material Cabinet: 1119 x 656 x 637 mm (44 x 25.8 x 25.1 in.); 153 kg (337 lbs Fabric Alignment Station: 91 X 81 X 215 cm; 142 kg Temperature 18 - 25 °C (64 - 77 °F); relative humidity 30-7 100-120 VAC, 50-60 Hz, 13.5 A, 1 phase; 220-240 VAC, 50 CE, FCC, EAC, RCM, R-NZ1 GrabCAD Print - GrabCAD Printer Connectivity SDK High Mix: up to 7 base resins, 27-micron (0.001 in.) resoluti High Speed: up to 3 base resins, 27-micron (0.001 in.) resoluti	8 lbs.) 70% (non-con 0–60 Hz, 7 A on ution sions, for mor 0.06% of par %) of models	densing) , 1 phase dels printed wi t length, which	ever is greater.	





stratasys.com ISO 9001:2015 Certified Stratasys Headquarters

7665 Commerce Way, Eden Prairie, MN 55344

- +1 800 801 6491 (US Toll Free)
- +1 952 937-3000 (Intl)
- +1 952 937-0070 (Fax)

1 Holtzman St., Science Park, PO Box 2496 Rehovot 76124, Israel +972 74 745 4000 +972 74 745 5000 (Fax)

Brochure 3DFashion

© 2024 Stratasys Ltd. All rights reserved. Stratasys, Stratasys signet J850, TechStyle, 3DFashion, Mindful Manufacturing, 3D Printing a Better Tomorrow, GrabCAD Print, Vero, VeroVivid, VeroEco, Agilus30, VeroClear, VeroUltraClear, VeroContactFlex, VeroEco, SUP705 and SUP706B are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners. Product specifications are subject to change without notice. BR_3DF_TechStyle_0110a