

Designed and built for size, throughput, precision and repeatability.

The **Stratasys F900**® is one of the most precise and powerful **FDM**® systems available. With the largest build size of any Stratasys FDM system, the Stratasys F900 is designed to handle the most demanding manufacturing needs. The accuracy, repeatability and predictability are unmatched, and the control software leverages the system's hardware to deliver superior throughput and reliability.

The Stratasys F900 uses Stratasys Preferred and Validated thermoplastics to build robust production parts, jigs, fixtures, factory tooling and functional prototypes. Large parts are printed fast with the optional 0.508 mm (0.020 in.) layer height to help meet production demands with ease. OpenAM™ software enables the use of third-party open materials and lets users alter machine print parameters to optimize material capabilities and print results.

The F900 offers an internal camera for easier job monitoring and a streamlined workflow enabled by GrabCAD Print software and MTConnect readiness. Data security, including U.S. Department of Defense STIG compliance, is provided by Stratasys ProtectAM™ technology. Standard certifications are included and reduce workload to qualify 3D printers for a production floor.

There is a material delivery and drying cabinet, the Fortus FDC™, that pairs with the F900 to extend printing times. This add-on feature can deliver up to 8,194 cm³ (500 in³) of model material. The cabinet also dries the spools of filament and maintains the environment so that moisture is never a concern - even when printing with moisture sensitive materials. The larger volume of material on the spools coupled with the drying capability improve reliability, print performance, uptime, and can reduce labor required to reload material.

System Specifications

Build Envelope (XYZ)	914.4 x 609.6 x 914.4 mm (36 x 24 x 36 in.) Platen supports two build zones for either a small or large build sheet
Material Delivery	Two model material canisters 1,508 cm ³ (92 in. ³); Two support material canisters 1,508 cm ³ (92 in. ³) Auto changeover between canisters. Fortus FDC™ allows for two model material canisters 4,097 cm ³ (250 in. ³) each.

Other Specifications

System Size and Weight	2,772 x 1,683 x 2,027 mm (109.1 x 66.3 x 79.8 in.); 2,869 kg (6,325 lbs.) With Manufacturing Light Tower: 2,772 x 1,683 x 2,281 mm (109.1 x 66.3 x 89.8 in.)
Achievable Accuracy	Parts are produced within an accuracy of +/- 0.089 mm or +/- 0.0015 mm per mm whichever is greater (+/- 0.0035 in. or +/- .0015 in. per in. whichever is greater).+ Z part accuracy includes an additional tolerance of -0.000/+ slice height. Note: Accuracy is geometry-dependent. Achievable accuracy specification derived from statistical data at 95% dimensional yield. See Fortus 900mc accuracy white paper for more information.
Network Communication	Wired: TCP/IPV6 protocols, 10/100 base T connection, Ethernet protocol
Operator Attendance	Limited attendance for job start and stop required
Operating Environment	Maximum room temperature of 29 °C (85 °F). Maximum room humidity of 80%
Power Requirements	230 VAC (three phase) 50/60Hz, Voltage fluctuation +/- Current 40A
Additional Requirements	Compressed Air Required 90-120 psi with a minimum flow of 20 CFM
Regulatory Compliance	CE, cTUVus, RCM, EAC, FCC Part B
Software	All Fortus systems include Insight and Control Center™ job processing and management software. Compatible with GrabCAD Print and GrabCAD Streamline Pro™ for use with job reports, scheduling and remote monitoring. U.S. government agency STIG compliance via Stratasys ProtectAM technology is powered by Red Hat® Enterprise Linux® software. GrabCAD Print Pro is available with a paid subscription and OpenAM software is available with the purchase of an OpenAM license.
Operating System	Insight: Microsoft Windows 11, Microsoft Windows 10, or Microsoft Windows Server 2012 R2 GrabCAD Print, GrabCAD Print Pro, and OpenAM: Windows 10 and newer, Windows Server 2016 and newer. Only 64-bit versions of Windows are supported.

Material Options

Stratasys Preferred Materials

Material	Layer Thickness					Support Structure	Available Colors	
	0.127 mm (0.005 in.)	0.178 mm (0.007 in.)	0.254 mm (0.010 in.)	0.330 mm (0.013 in.)	0.508 mm (0.020 in.)			
ABS-ESD7™	○	●	●	○	○	Soluble	■ Black	
ABS-M30i™	○	●	●	●	○	Soluble	■ Ivory	
ABS-M30™	○	●	●	●	○	Soluble	■ Ivory □ White ■ Black	■ Red ■ Blue ■ Dark Gray
Antero® 800NA	○	○	●	○	○	Breakaway	■ Natural	
Antero® 840CN03	○	○	●	○	○	Breakaway	■ Natural	
ASA	●	●	●	●	●	Soluble	■ Black ■ Dark Gray ■ Light Gray □ White ■ Ivory	■ Dark Blue ■ Green ■ Yellow ■ Orange ■ Red
FDM® Nylon 6	○	○	●	●	○	Soluble	■ Black	
FDM® Nylon 12	○	●	●	●	○	Soluble	■ Black	
FDM® Nylon 12CF™	○	○	●	○	●	Soluble	■ Black	
FDM® PA6/66-GF30-FR	○	○	●	○	○	Breakaway	■ Black	
PC	○	●	●	●	○	Breakaway, Soluble	□ White	
PC-ABS	○	●	●	●	○	Soluble	■ Black	
PC-ISO™	○	●	●	●	○	Breakaway	■ Translucent Natural □ White	
PPSF	○	○	●	○	○	Breakaway	■ Tan	
ST-130™	○	○	○	●	○	Breakaway	■ Natural	
ULTEM™ 1010 resin	○	○	●	●	●	Breakaway	■ Natural	
ULTEM™ 1010 resin CG	○	○	●	●	●	Breakaway	■ Natural	
ULTEM™ 9085 resin	○	○	●	●	●	Breakaway	■ Tan ■ Black	
ULTEM™ 9085 resin CG	○	○	●	●	●	Breakaway	■ Tan ■ Black	

Material Options

Stratasys Validated Materials

Material	Layer Thickness				Support Structure	Available Colors
	0.127 mm (0.005 in.)	0.178 mm (0.007 in.)	0.254 mm (0.010 in.)	0.330 mm (0.013 in.)		
FDM® HIPS	○	○	●	○	Breakaway	■ Light Gray
PC (colors)	○	○	●	○	Soluble	■ Red
PC-ABS (colors)	○	○	●	○	Soluble	■ Red
PC-ESD	○	○	●	○	Soluble	■ Black
ULTEM™ 9085 resin (colors)	○	○	●	●	Breakaway	■ Red
	○	○	●	○	Breakaway	■ Jana White
	○	○	●	○	Breakaway	■ Dream Gray
	○	○	●	○	Breakaway	□ White 7362
	○	○	●	○	Breakaway	■ Gunship Gray
VICTREX AM™ 200	○	○	●	●	Breakaway	■ Aircraft Gray
	○	○	●	○	Breakaway, Soluble	■ Natural



stratasys.com
ISO 9001:2015
Certified

Stratasys Headquarters
5995 Opus Parkway,
Minnetonka, MN 55343
+1 800 801 6491 (US Toll Free)
+1 952 937-3000 (Intl)
+1 952 937-0070 (Fax)

1 Holtzman St.
Science Park
Rehovot, 7670401
Israel
+972 74 745 4000
+972 74 745 5000 (Fax)

PRODUCT SPEC SHEET FDM

© 2026 Stratasys. All rights reserved. Stratasys, FDM, F900 and Fortus are registered trademarks of Stratasys Inc. GrabCAD Print, GrabCAD Print Pro, GrabCAD Streamline Pro, OpenAM, ProtectAM, Insight, ABS-M30, ABS-M30i, ABS-ESD7, PC-ISO, FDM Nylon 6, FDM Nylon 12, FDM Nylon 12CF, Antero 800NA, Antero 840CN03 and ST-130 are trademarks of Stratasys, Inc. 9085, 1010 and ULTEM™ are trademarks of SABIC, its affiliates or subsidiaries. VICTREX AM™ 200 is a trademark of Victrex Manufacturing Ltd. Red Hat is a registered trademark of Red Hat, Inc. in the United States and other countries. All other trademarks are the property of their respective owners, and Stratasys assumes no responsibility with regard to the selection, performance, or use of these non-Stratasys products. Product specifications subject to change without notice. PSS_FDM_F900_0526a